

MOC 10

no name

type of gauging

IF
INNAGE,
ENTER
'X', IF
ULLAGE
ENTER
'O'

compartment	LBDM IN FT	length in feet	distance from aft bulkhead(ft)	Ullage TRIM inches down by stern
1 PORT	224	56.85	2	1 3/8
1 STAR		56.85	2	1 3/8
2 PORT		64.75	1.5	1 5/8
2 STAR		64.75	1.5	1 5/8
3 PORT		56.75	1.5	1 4/8
3 STAR		56.71	1.5	1 4/8
4 PORT		72.75	71.25	-1 7/8
4 STAR		72.75	71.25	-1 7/8



BARGE "MOC 10" ULLAGE TRIM CORRECTIONS

Down by	1 ft		2 ft		3 ft		4 ft		5 ft		6 ft	
	BOW	STERN	BOW	STERN	BOW	STERN	BOW	STERN	BOW	STERN	BOW	STERN
1 PORT	-01- 3/8	01- 3/8	-02- 7/8	02- 7/8	-04- 2/8	04- 2/8	-05- 5/8	05- 5/8	-07- 1/8	07- 1/8	-08- 4/8	08- 4/8
1 STAR	-01- 3/8	01- 3/8	-02- 7/8	02- 7/8	-04- 2/8	04- 2/8	-05- 5/8	05- 5/8	-07- 1/8	07- 1/8	-08- 4/8	08- 4/8
2 PORT	-01- 5/8	01- 5/8	-03- 2/8	03- 2/8	-05	05	-06- 5/8	06- 5/8	-08- 2/8	08- 2/8	-09- 7/8	09- 7/8
2 STAR	-01- 5/8	01- 5/8	-03- 2/8	03- 2/8	-05	05	-06- 5/8	06- 5/8	-08- 2/8	08- 2/8	-09- 7/8	09- 7/8
3 PORT	-01- 4/8	01- 4/8	-02- 7/8	02- 7/8	-04- 3/8	04- 3/8	-05- 6/8	05- 6/8	-07- 2/8	07- 2/8	-08- 5/8	08- 5/8
3 STAR	-01- 4/8	01- 4/8	-02- 7/8	02- 7/8	-04- 3/8	04- 3/8	-05- 6/8	05- 6/8	-07- 2/8	07- 2/8	-08- 5/8	08- 5/8
4 PORT	01- 7/8	-01- 7/8	03- 6/8	-03- 6/8	05- 5/8	-05- 5/8	07- 4/8	-07- 4/8	09- 3/8	-09- 3/8	11- 2/8	-11- 2/8
4 STAR	01- 7/8	-01- 7/8	03- 6/8	-03- 6/8	05- 5/8	-05- 5/8	07- 4/8	-07- 4/8	09- 3/8	-09- 3/8	11- 2/8	-11- 2/8

EXAMPLE FOR USE OF TRIM CORRECTION:

FWD DRAFT = 3'-0"

AFT DRAFT = 6'-0"

DIFFERENCE = 3'-0" (DOWN BY STERN)

TRIM CORRECTION FOR 3'-0" DOWN BY STERN FOR 1 PORT IS 0'- 04-2/8 "

TO OBSERVED ULLAGE GAUGE OF 3'-0" THE TRIM CORRECTED ULLAGE IS 3'- 04-2/8 "

LENGTH BETWEEN DRAFT MARKS =

224'

COMPUTED BY: JF 01/26/05
 GAUGE LOCATIONS MEASURED BY: BC 01/21/05
 STRAPPED BY: CLJ-CEK-TM 06/21/73